

Rotulas SI SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
SIL 40 T/K			d	G	B	C ₁	d ₂	d ₃	d ₄
			40	M 42 x 2	49	33,00	91	53,0	65

type	measurement [mm]				load rating C ₅ [kN]	weight [kg]
	l ₃ min	W	h	d ₁		
SI / SIL 40 T/K	60	55	142	17		2,400

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489810
Diámetro interior	40 mm
Diámetro exterior	91 mm
Espesor	49 mm
Tipo	SI
Peso	2400 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE