

## Rotulas SA SAL8-T-K-DURBAL - SAL8-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/sal8-t-k-durbal>


### SAL8-T-K



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
SAL 8 T/K		8	M 8	12	9,00	24	
type	l <sub>1</sub> min	measurement [mm]		h	alpha [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
SA / SAL 8 T/K	25			42	14	12,9	0,038

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952490007
Diámetro interior	8 mm
Diámetro exterior	24 mm
Espesor	12 mm
Tipo	SA
Peso	38 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	-
Estándar	Ninguna norma

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE