

# Rotulas SI

## DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/dssi5-t-k-durbal>

### DSSI5-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	d	G	measurement [mm]					
right hand thread	left hand thread		B	C1	d1	d2	d3	d4
DSSI 5 T/K		5 M 5	8	6,00	18	8,5	11	

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952491059
Diámetro interior	5 mm
Diámetro exterior	18 mm
Espesor	8 mm
Tipo	SI
Peso	16 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE