

Rotulas SI

GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/gir70-uk-2rs-durbal>

GIR70-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]				
GIR 70 UK-2RS	d 70	G M 56 x 4			
	B 49	C ₁ 42,0			
	d ₂ 160	d ₃ 80,0			
	d ₄ 98				
type	measurement [mm]		load rating	weight	
GIR / GIL 70 UK-2RS	l ₃ min 80	h 200	W 85	C ₀ (kN) 610,0	kg 8,600

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952494296
Diámetro interior	70 mm
Diámetro exterior	160 mm
Espesor	49 mm
Tipo	SI
Peso	8600 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE