

## Rotulas SI SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/si25-es-2rs-durbal>

### SI25-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**order number**  
right hand thread    left hand thread

SI 25 ES (-2RS)	d	G	measurement (mm)				
			B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	
	25	M 24 x 2	20	17,0	64	33,5	42

**measurement [mm]**

type	l <sub>3</sub> min	measurement [mm]			load rating C <sub>0</sub> [kN]	weight [g]
		W	h	$\alpha$ [°]		
SI / SII 25 ES (-2RS)	48	36	94	7	83,0	0,64

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952497198
Diámetro interior	25 mm
Diámetro exterior	64 mm
Espesor	20 mm
Tipo	SI
Peso	640 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE