

Rotulas SI

SIL80-ES-2RS-DURBAL - DSIL80-ES-2RS-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/dsil80-es-2rs-durbal>

SIL80-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSIL...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
		d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 80 ES (-2RS)		80	M 64 x 4	55	47,0	180	95,0	110

type

	l ₃ min	W	h	α	load rating C ₀ (kN)	weight (kg)
SI / SIL 80 ES (-2RS)	85	100	230	6	750,0	12,0

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952497839
Diámetro interior	80 mm
Diámetro exterior	180 mm
Espesor	55 mm
Tipo	SI
Peso	12000 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE