

Rotulas SA SAL20-ES-DURBAL - DSAL20-ES-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/dsal20-es-durbal>

SAL20-ES



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Bad end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 20 ES	20	M 20 x 1,5	16	13,0	53

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 20 ES	43	27	78		9	60,0	0,310

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952498232
Diámetro interior	20 mm
Diámetro exterior	53 mm
Espesor	16 mm
Tipo	SA
Peso	310 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE