

## Rotulas TAPR

### GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/tapr/giho-k-16do-durbal

**GIHO-K-16DO**

female thread:  
hydraulic rod ends,  
according to  
DIN 24555

**FERROBAL**

\* without grease nipple

**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>	B	C <sub>1</sub>	C <sub>2</sub>	
GIHO-K 16 DO*		16	20,7	45	M 12 x 1,25	21	45	14	11	13	

type	measurement [mm]				α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952500652
Diámetro interior	16 mm
Diámetro exterior	45 mm
Espesor	11 mm
Tipo	TAPR
Peso	220 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE