

Rotulas TAPR

GIHO-K-30DO-DURBAL - GIHO-K-30DO-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/tapr/giho-k-30do-durbal

GIHO-K-30DO

Female thread:
hydraulic rod ends,
according to
DIN 24555

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

* without grease nipple

order number	right hand thread		left hand thread		measurement [mm]						
	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂		
GIHO-K 30 DO	30	34,2	80	M 20 x 1,5	36	77	22	19	19		

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952500768
Diámetro interior	30 mm
Diámetro exterior	80 mm
Espesor	19 mm
Tipo	TAPR
Peso	1250 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE