

Rotulas GEG GE60-LO-DURBAL - GE60-LO-DURBAL


<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/geg/ge60-lo-durbal>

GE60-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	measurement [mm]				
	d	B	C	d ₁ min	D
GE 60 LO	60	60	36	68,0	90

type	measurement [mm]		d ₁	α [°]	load rating C ₁₀ [N]	weight [kg]
	r ₁₅ min	r ₂₅ min				
GE 60 LO	1,0	1,0	80,0	4	1220	1,150

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952506517
Diámetro interior	60 mm
Diámetro exterior	90 mm
Espesor	36 mm
Tipo	GEG
Peso	1150 g
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE