

Rotulas SA

BRTM20-00-501-DURBAL - BRTM20-00-501-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/brtm20-00-501-durbal>

BRTM20-00-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


liner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]							
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	b ₁	b ₂	b ₃
BRTM 20 -00	-501		20	M 20 x 1,5	24,5	50	25		18
measurements [mm]		weight		rotational speed limit		basic load rating		stat.	
type	h	l	b ₃	α [°]	[kg]	n _{max} [rpm]	C [N]	C ₁₀ [N]	C ₅₀ [N]
BRTM 20	78	47	28	7,0	0,340	825	17000		11700

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952506760
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	SA
Peso	340 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE