

Rotulas GE

BRTM30-00-501-DURBAL - BRTM30-00-501-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/brtm30-00-501-durbal>

BRTM30-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number			measurements [mm]						
type	type hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	b ₁	b ₂	b ₃
BRTM 30 -00	-501		30	M 30 x 2	34,5	70	37		25
measurements [mm]			weight		rotational speed limit	basic load rating		dyn. stat.	
type	h	l	b ₃	α [°]	[kg]	n _{max} [rpm]	C [N]	C ₁₀ [N]	C ₅₀ [N]
BRTM 30	110	66	35	7,5	0,912	450	32500		24850

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3616060468178
Diámetro interior	30 mm
Diámetro exterior	70 mm
Espesor	37 mm
Tipo	GE
Peso	912 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE