

Rotulas SI

BRTF20-00-502-DURBAL - BRTF20-00-502-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/brtf20-00-502-durbal>

BRTF20-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂
BRTF 20 -00		-502	20	27,5	M 20 x 1,5	24,5	50	34	25	18	

type	measurements [mm]					weight [kg]	rotational speed limit n _{max} [min ⁻¹]	basic load rating		
	h	l	l ₁	l ₃	SW			C [N]	stat. C ₀ [N]	
BRTF 20	77	33	10,0	26	30	7,0	0,361	825	17000	11700

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952506876
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	SI
Peso	361 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE