

# Rotulas SI

## PF15-00-502-DURBAL - PF15-00-502-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/pf15-00-502-durbal>

### PF15-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminum-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA HI

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields

order number		measurements [mm]										
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>		
PF 15 -00		-502	15	19	M 12	17,5	40	16,5	12			
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	l <sub>1</sub>	r	SW	α	Y	Y <sub>0</sub>	lim [min]	C	C <sub>0</sub>	
PF 15	51	24	20,0	15	17	7,0	0,140	2,30	2,41	1025	5000	1890

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952507385
Diámetro interior	15 mm
Diámetro exterior	40 mm
Espesor	16.5 mm
Tipo	SI
Peso	140 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE