

Rotulas SA

PM05-01-502-DURBAL - PM05-01-502-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm05-01-502-durbal

PM05-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C	C0	C00
PM 05 -01	-502	5	M 8 x 1		7,5	19	12	12	12	8						
measurements [mm]		weight			rotational speed limit			basic load rating								
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	weight [kg]	Y	Yc	nmax [min-1]	C	C0	C00
PM 05	16	13	33,5	1,5	2,5	7,0				0,033	1,51	1,58	1350	1610	480	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952507446
Diámetro interior	5 mm
Diámetro exterior	19 mm
Espesor	12 mm
Tipo	SA
Peso	33 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE