

Rotulas SA

PM05-01-501-DURBAL - PM05-01-501-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm05-01-501-durbal

PM05-01-501

male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating		
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₀ [N]
PM 05 -01	-501	5	M 8 x 1		7,5	19	12	12	12	8						
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]						
PM 05	16	13	33,5		1,5	2,5	7,0			0,033	1,51	1,58	1350	1610	480	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507453
Diámetro interior	5 mm
Diámetro exterior	19 mm
Espesor	12 mm
Tipo	SA
Peso	33 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE