


Rotulas SA

PM06-02-501-DURBAL - PM06-02-501-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm06-02-501-durbal

PM06-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating		
type	type	d1	d2	d4	d7	b1	b2	Y	Yc	C	C0	
PM 06 -02 -501		6	M 10 x 1	8,5	24	14	14	10				
measurements [mm]		weight		rotational speed limit		basic load rating						
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	Yc	
PM 06 19	17	40,5		1,5	2,5	10,5	0,057	1,28	1,34	1300	2445	765

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507491
Diámetro interior	6 mm
Diámetro exterior	24 mm
Espesor	14 mm
Tipo	SA
Peso	57 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE