


Rotulas SA

PM15-00-501-DURBAL - PM15-00-501-DURBAL


https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm15-00-501-durbal

PM15-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C	C0	dyn. [N]	stat. [N]		
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14											
type	l1	l2	l3	h1	h2	u	z	alpha [°]	weight [kg]	Y	Yc	nmax [min-1]	C	C0	dyn. [N]	stat. [N]			
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17	975	5485	3270							

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507620
Diámetro interior	15 mm
Diámetro exterior	42 mm
Espesor	20 mm
Tipo	SA
Peso	310 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE