


# Rotulas SA

## PM15-00-501-DURBAL - PM15-00-501-DURBAL


https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm15-00-501-durbal

### PM15-00-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISOA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]					measurements [mm]					weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C	C0	dyn. [N]	stat. [N]		
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14											
measurements [mm]		weight			rotational speed limit			basic load rating											
type	l1	l2	l3	h1	h2	u	z	alpha [°]	weight [kg]	Y	Yc	nmax [min-1]	C	C0	dyn. [N]	stat. [N]			
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17	975	5485	3270							

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952507620
Diámetro interior	15 mm
Diámetro exterior	42 mm
Espesor	20 mm
Tipo	SA
Peso	310 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE