

Rotulas SA

PM17-00-502-DURBAL - PM17-00-502-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm17-00-502-durbal

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	type	d1	d2	d4	d5	d7	b1	b2	Y	Yc	C	C0	
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16					
measurements [mm]		weight		rotational speed limit		basic load rating							
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	weight [kg]	rotational speed limit [min-1]	basic load rating [N]	basic load rating [kN]
PM 17	62,5	36	105	3,5	2,5	7,0	0,401	2,35	2,46	875	5575	2680	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952507675
Diámetro interior	17 mm
Diámetro exterior	48 mm
Espesor	22 mm
Tipo	SA
Peso	401 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE