

Rotulas SA

PM20-02-501-DURBAL - PM20-02-501-DURBAL

https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/sa/pm20-02-501-durbal

PM20-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		rotational speed limit		basic load rating	
type	sp. thread	d ₁	d ₂	d ₄	d ₅	Y	Y ₀	C	C ₀
PM 20 -02	-501	20	M 24 x 1,5	24,0	56	2,76	2,90	775	6165

measurements [mm]		weight		rotational speed limit		basic load rating							
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	Y	Y ₀	C	C ₀	
PM 20	41	41	89,5	3,5	3,0	5,5			2,76	2,90	775	6165	3140

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952507736
Diámetro interior	20 mm
Diámetro exterior	56 mm
Espesor	24 mm
Tipo	SA
Peso	519 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE