

Rotulas GE

BRF06-60-501-DURBAL - BRF06-60-501-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/brf06-60-501-durbal>

BRF06-60-501



rod end housing:
stainless steel 1.4534, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminum-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]											
type	light load thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h		
BRF 06 -60	-501	6	10,0	M 6	9,0	20	13	9	6,75	30			
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.			
type	l	l ₁	l ₂	SW	α [°]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₁₀	C ₅₀	stat. [N]
BRF 06	12	5,0	10	11	8,0	0,024	2,09	2,19	1350	1900	450		

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3616060468260
Diámetro interior	6 mm
Diámetro exterior	20 mm
Espesor	9 mm
Tipo	GE
Peso	24 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE