


Rotulas SI

BRF20-60-501-DURBAL - BRF20-60-501-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/brf20-60-501-durbal>

BRF20-60-501 

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished


lubrication:
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel



female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



| order number | | measurements [mm] | | | | | | | | | | | |
|------------------------|-------------------|-------------------|---------------------|------------------------|-------------------|-------|-------|----------------|-------------|------|----------------|-------|--|
| type | light load thread | light load thread | M 20 x 1,5 | 24,5 | 50 | 34 | 25 | 18,0 | 77 | | | | |
| BRF 20 -60 -501 | | | | | | | | | | | | | |
| measurements [mm] | | weight | calculation-factors | rotational speed limit | basic load rating | | stat. | | | | | | |
| type | l | l ₁ | l ₂ | SW | α [°] | [kg] | Y | Y ₀ | speed limit | C | C ₀ | stat. | |
| BRF 20 | 33 | 10,0 | 26 | 30 | 7,0 | 0,367 | 2,46 | 2,58 | 825 | 5350 | 2300 | | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | DURBAL |
| Nº Ean13 | 3663952509310 |
| Diámetro interior | 20 mm |
| Diámetro exterior | 50 mm |
| Espesor | 25 mm |
| Tipo | SI |
| Peso | 367 g |
| Hilo | Rosca derecha |
| Lubricación | con |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE