


Rotulas SI

BRTF1-1-00-502-DURBAL - BRTF1-1-00-502-DURBAL

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/si/brtf1-1-00-502-durbal>

BRTF1/1-00-502 

red end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1



lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, dimensions in inches

order number		measurements [inches]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂
BRTF 1/1 -00	-502		1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866	
		measurements [inches]									
type	h	l	l ₁	l ₂	SW	α [°]	weight [kg]	rotational speed limit [min ⁻¹]	basic load rating C [N]	stat. C ₁₀ [N]	
BRTF 1/1	3.720	1.653	.236	1.279	1.181	5.0	0.568	600	24900	18500	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952510064
Diámetro interior	25.4 mm
Diámetro exterior	63.98 mm
Espesor	30.99 mm
Tipo	SI
Peso	568 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE