


## Casquillos de agujas FC-30-NADELLA - FC-30-NADELLA

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/fc-30-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F <sub>o</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
30	FC-30	30	37	20	99.1	7300	HK3012

Shaft Ø mm	Gapping			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
30	36.972	29.967	30.007	51	Max. mm: 30.000	Min. mm: 29.991	Max. mm: 36.988	Min. mm: 36.972	0.042

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NADELLA
N° Ean13	3663952529493
Diámetro interior	30 mm
Diámetro exterior	37 mm
Espesor	20 mm
Peso	42 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE