







## Rodamiento de bolas una hilera 1614-SS-NICE - 1614-SS-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/1614-ss-nice>

**1600** Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS	
BEARING						
	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	
					SS	
					BORE <b>d</b> (in) (mm)	O.D. <b>D</b> (in) (mm)
					+0.000 +0.00 -0.0005 -0.013	+0.000 +0.00 -0.0005 -0.013
1614™					0.3750 9.525	1.250 28.575
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH <b>B</b> (in) (mm)	DYNAMIC <b>C</b> (lb) (N)	STATIC <b>C<sub>0</sub></b> (lb) (N)	<b>W<sup>0</sup></b> (lb) (g)	<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)
+0.000 +0.00 -0.005 -0.13	1200 5340	475 2114	0.06 0.03	0.595 15.11	1.014 25.76	0.025 0.64
<small>ⓘ Weights given are for greased and sealed versions</small>						

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952557236
Diámetro interior	9.525 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE