






Rodamiento de bolas una hilera 1616-SC-NICE - 1616-SC-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/1616-sc-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS	
BEARING						
	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	
1616™		SC				
	BORE d (in) (mm)	O.D. D (in) (mm)				
	+0.000 +0.00 -0.0005 -0.013	+0.000 +0.00 -0.0005 -0.013				
	0.5000 12.700	1.1250 28.575				
BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C₀ (lb) (N)	W⁰ (lb) (g)	d_a min (in) (mm)	D_a max (in) (mm)	r max (in) (mm)
+0.000 +0.00 -0.005 -0.13	1200 5340	475 2114	0.06 0.03	0.622 15.90	1.014 25.76	0.025 0.64

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952557311
Diámetro interior	12.7 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE