

Rodamiento de bolas una hilera 1623-SC-NICE - 1623-SC-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/1623-sc-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
	+0.000 +0.00 -0.005 -0.13					-0.0000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.0005 -0.013
1623™		SC				0.6250 15.875	1.2750 34.925
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.4375 11.113	1878 8367	850 3783	0.10 0.05	0.753 19.13	1.203 30.56	0.025 0.64	

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952557489
Diámetro interior	15.875 mm
Diámetro interior	5/8" inch
Diámetro exterior	34.925 mm
Diámetro exterior	1 3/8" inch
Espesor	11.113 mm
Espesor	7/16" inch
Peso	50 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE