

Rodamiento de bolas una hilera 1630-SS-NICE - 1630-SS-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/1630-ss-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
1630™					SS	0.7000 19.050	1.8250 41.275
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.5000 12.700	2595 11548	1010 4495	0.18 0.07	0.965 24.51	1.446 36.73	0.025 0.64	

Weights given are for greased and sealed versions

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952557564
Diámetro interior	19.05 mm
Diámetro exterior	41.275 mm
Espesor	12.7 mm
Peso	70 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE