



Rodamiento de bolas una hilera 3003-NS-NICE - 3003-NS-NICE






<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3003-ns-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

NICE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE d (in) (mm) +0.005 +0.13 -0.000 -0.00	O.D. D (in) (mm) +0.000 +0.00 -0.0005 -0.013
3003™					NS	0.3125 7.938	0.8750 22.225

WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	BASIC LOAD RATINGS		WEIGHT W (lb) (kg) 0.03 0.01	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N) 325 1446	STATIC Co (lb) (N) 255 1135		da min (in) (mm) 0.474 12.04	Da max (in) (mm) 0.778 19.76	r max (in) (mm) 0.012 0.30
0.2813 7.145	325 1446	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.012 0.30

Ⓞ Width for sealed versions = 0.3438 (8.733)
 Ⓞ Weights given are for greased and sealed versions
Ⓞ 3038 and larger +0.0005/-0.005 (+0.001/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558097
Diámetro interior	7.938 mm
Diámetro exterior	22.225 mm
Espesor	7.145 mm
Peso	10 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE