




## Rodamiento de bolas una hilera 3007-DS-NICE - 3007-DS-NICE






<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3007-ds-nice>

**3000 Series® Semi-Ground Radial Bearings**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINERS STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.00	+0.000 +0.00 -0.013
3007™				DS		0.4375 11.113	0.9063 23.020

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
+0.005 +0.00 -0.005 -0.13	350 1568	300 1355	0.03 0.07	0.517 13.13	0.778 19.76	0.015 0.38	

Ⓞ Weights given are for greased and sealed versions  
 Ⓞ 3038 and larger +0.000/-0.006 (-0.00/-0.15)

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558271
Diámetro interior	11.113 mm
Diámetro exterior	23.02 mm
Espesor	7.938 mm
Peso	10 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE