

Rodamiento de bolas una hilera 3015-SC-NICE - 3015-SC-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3015-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3015™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
						0.4375 11.113	1.1250 28.575

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	C (lbs) (N)	Co (lbs) (N)	W (lbs) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
0.3750 9.525	600 2670	475 2114	0.06 0.03	0.622 15.80	1.014 25.76	0.025 0.64	

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3015 and larger +0.0005/-0.005 (+0.001/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558363
Diámetro interior	11.113 mm
Diámetro interior	7/16" inch
Diámetro exterior	28.575 mm
Diámetro exterior	1 1/8" inch
Espesor	9.525 mm
Espesor	3/8" inch
Peso	30 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE