


## Rodamiento de bolas una hilera 3016-NS-NICE - 3016-NS-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3016-ns-nice>

**3000 Series® Semi-Ground Radial Bearings**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- RFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



**NICE®**

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE <b>d</b> (in) (mm)	O.D. <b>D</b> (in) (mm)
	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	+0.005 -0.13 -0.000	+0.000 +0.00 -0.005
3016™					NS	0.5000 12.700	1.1250 28.575

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
<b>B</b> (in) (mm)	<b>C</b> (lbs) (N)	<b>Co</b> (lbs) (N)	<b>W</b> (lbs) (kg)	<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)	
+0.005 +0.00 -0.005 -0.13	600 2670	475 2114	0.06 0.03	0.622 15.80	1.014 25.76	0.025 0.64	

Ⓞ Weights given are for greased and sealed versions  
 Ⓞ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

## CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952558400
Diámetro interior	12.7 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE