







Rodamiento de bolas una hilera 3016-SC-NICE - 3016-SC-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3016-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS	
BEARING						
	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	
3016™		SC				
	BORE	O.D.				
	d	D				
	(in)	(in)				
	(mm)	(mm)				
	+0.005	+0.000				
	+0.13	+00				
	-0.000	-0.005				
	-0.00	-0.013				
	0.5000	1.1250				
	12.700	28.575				

WIDTH	BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC	STATIC		d _a min	D _a max	r max
B	C	Co	W	d _a min	D _a max	r max
(in)	(lbs)	(lbs)	(lbs)	(in)	(in)	(in)
(mm)	(N)	(N)	(kg)	(mm)	(mm)	(mm)
+0.005						
+0.00	600	475	0.06	0.622	1.014	0.025
-0.005	2670	2114	0.03	15.80	25.76	0.64
-0.13						

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.0000/-0.005 (-0.000/-0.13)

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952558431
Diámetro interior	12.7 mm
Diámetro exterior	28.575 mm
Espesor	9.525 mm
Peso	30 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE