


## Rodamiento de bolas una hilera 3020-SC-NICE - 3020-SC-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/3020-sc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



| SUFFIX  |             |             |               |               |      | PRINCIPLE DIMENSIONS                |                            |
|---------|-------------|-------------|---------------|---------------|------|-------------------------------------|----------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE<br>d<br>(in)<br>(mm)           | O.D.<br>D<br>(in)<br>(mm)  |
| 3020™   |             |             |               |               |      | +0.005<br>-0.13<br>-0.000<br>-0.000 | +0.000<br>+0.00<br>-0.0005 |
|         |             |             |               |               | SC   | 0.4375<br>11.113                    | 1.3750<br>34.925           |

| BASIC LOAD RATINGS         |                             |                             | WEIGHT            | ABUTMENT AND FILLET DIMENSIONS |                        |                       |
|----------------------------|-----------------------------|-----------------------------|-------------------|--------------------------------|------------------------|-----------------------|
| WIDTH<br>B<br>(in)<br>(mm) | DYNAMIC<br>C<br>(lb)<br>(N) | STATIC<br>Co<br>(lb)<br>(N) | W<br>(lb)<br>(kg) | da min<br>(in)<br>(mm)         | Da max<br>(in)<br>(mm) | r max<br>(in)<br>(mm) |
| 0.4375<br>11.113           | 940<br>4183                 | 860<br>3783                 | 0.12<br>0.05      | 0.658<br>16.71                 | 1.203<br>30.56         | 0.025<br>0.64         |

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3020 and larger +0.0005/-0.005 (-0.000/-0.13)

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | NICE          |
| N° Ean13          | 3663952558462 |
| Diámetro interior | 11.113 mm     |
| Diámetro exterior | 34.925 mm     |
| Espesor           | 11.113 mm     |
| Peso              | 50 g          |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE