


## Rodamiento de bolas una hilera 5418-V-NICE - 5418-V-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-bola/una-hilera/5418-v-nice>

**5000** Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5418™	V	1.000 +0.005/-0.000 25.40	2.069 +0.005/+0.000 52.50	0.872 +0.010/-0.010 22.15	0.980 14.53	2.125 53.98	0.218 5.54	0.718 +0.010/-0.010 18.24

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (in) (%)	100 (in) (%)	200 (in) (%)	300 (in) (%)	600 (in) (%)	1200 (in) (%)	
17	1/4 6.35	0.30 0.14	757 3389	525 2338	362 1611	293 1304	204 908	142 632

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3663952560328
Diámetro interior	25.4 mm
Diámetro exterior	50.8 mm
2º Diámetro exterior	53.98 mm
Espesor	14.53 mm
2º Espesor	18.24 mm
Peso	140 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE