


Accesorio de cojinete 7618-DL-NICE - 7618-DL-NICE

<https://www.123rodamiento.mx/rodamiento-cojinete/cojinete/accesorio/7618-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- SHOCK RESISTANT
- WIPER CASE STANDARD
- SHOCK RESISTANT STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP CASE OPTION. THIS PRICE APPLIES TO AN OPTION.
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERFINISHING ARE REQUIRED.



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7618™ Ø	1.1250 28.58	2.5505 65.03	0.7500 19.05	0.0625 1.59	1.872 42.47	0.190 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)
0.095 1.65	2.768 70.25	1.417 35.98	1.417 35.98	0.605 15.37	0.261 6.63	1/4-28 0.095 0.89	5360 23852	2620 11659	0.80 0.36

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +.0000/-0.0005 (+.0001/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of NICE Bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
N° Ean13	3616060473493
Diámetro interior	28.58 mm
Diámetro exterior	42.47 mm
Espesor	19.05 mm
Peso	360 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE