

Rotulas GE GE50-FW-DUNLOP - GE50-FW-DUNLOP

<https://www.123rodamiento.mx/rodamiento-cojinete/rotulas/ge/ge50-fw-dunlop>

SPHERICAL BEARINGS

GE FW SERIES

Description:
GE-FW Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-53°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE50FW		50	36	36	90	1,150,000

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
N° Ean13	3616060557285
Diámetro interior	50 mm
Diámetro interior	1.969" inch
Diámetro exterior	56 mm
Diámetro exterior	2.205" inch
Espesor	36 mm
Espesor	1.417" inch
Tipo	GE
Lubricación	con
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE