

Pegamento 609-50ML-LOCTITE - 609-50ML-LOCTITE

<https://www.123rodamiento.mx/lubricante-adhesivo/adhesivo/pegamento/609-50ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Solidifiant ML/ASTM, anaérobie lubrifiant
NOM	LOCTITE 609
CONDITIONNEMENT	31 litres
APPROBATION*	

Description

LOCTITE 609 is a green, high strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts. The product cures in the absence of air between close fitting metal surfaces. Typical applications include rotor to shafts in fractional and subfractional horsepower motors. Locks bushings and sleeves in housings on shafts. Augments press fits.

Avantages

Low viscosity
Prevents loosening and leakage from shock and vibration
Augments press fits
Tested to the lot requirements of Military Specification MIL-R-46082B (this is a regional approval)

Caractéristiques

High strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts.



CARACTERÍSTICAS DEL PRODUCTO

Marca	LOCTITE
N° Ean13	4058093028117
Tipo	FIXATION ROULEMENT
Peso	83 g
Envasado	1
Utilice	Anaérobic

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE