

## Adhesivo

### EA-E04-50ML-LOCTITE - EA-E04-50ML-LOCTITE

<https://www.123rodamiento.mx/lubricante-adhesivo/adhesivo/adhesivo/ea-e04-50ml-loctite>

TITRE	Epoxy
DESCRIPTION	Epoxy bicomposant gris, viscosité élevée, rapide, ratio 1/1
NOM	LOCTITE EA E-04
CONDITIONNEMENT	Ca 2K50 ml
DANGEROUS GOODS	Yes
COMMENTAIRE	-
APPROBATION	-

**§ Description**

LOCTITE® EA E04 is a grey, 2-part, 1:1 epoxy resin adhesive. It is a very tough material used in structurally demanding applications which require excellent resistance to vibration and impact loading, combined with the benefit of a 3 h cure time but 30 min when heated at +60°C. Particularly suited to the assembly of composite structures made from SMC, DMC or 'wet lay-up' polyesters.

**∴ Avantages**

Very tough material used in structurally demanding applications. Excellent resistance in service to vibration and impact loading. Cures within 3 h but 30 min when heated at +60°C. Suited to wood, metal, plastics and ceramics but particularly suited to the assembly of composite structures made from SMC, DMC or 'wet lay-up' polyesters. Can withstand temperatures from -55 to +70°C. Over 20 years of proven performance in industry.

**☒ Caractéristiques**

grey, 2-part, 1:1 epoxy resin adhesive. Very tough material used in demanding applications which require resistance to vibration and impact loading.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	LOCTITE
N° Ean13	3616060816559
Tipo	COLLAGE RIGIDE EPOXY ACRYLIQUE
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE