


Rodamiento conico 30318-R-JTEKT - 30318-R-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/30318-r-jtekt>

Single-row tapered roller bearings
metric series **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
90	190	46.5	43	36	336	407	2 100	2 700	30318R	

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _a min.	d _a max.	D _a min.	D _a max.	S _a min.	S _a max.	r _a min.	r _a max.		Y ₁	Y ₀		
—	37.2	108	113	176	165	177	5	10.5	3	2.5	0.35	1.73	0.95	5.78

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250122347
Diámetro interior	90 mm
Diámetro exterior	190 mm
Espesor	46.5 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE