

## Rodamiento conico 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                     | Basic load ratings (kN) |                     |                     |                     | Limiting speeds (min <sup>-1</sup> ) |                     | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|---------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                   | C                       | C <sub>r</sub>      | C <sub>0r</sub>     | Grease lub.         | Oil lub.                             |                     |                           |                    |                |                      |      |
| 100                                    | 215                | 77.5                     | 73                  | 60                      | 579                 | 783                 | 1 800               | 2 400                                | 32320JR             |                           |                    |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                         |                     |                     |                     |                                      |                     | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>a</sub> min.      | d <sub>a</sub> max. | D <sub>a</sub> min.     | D <sub>a</sub> max. | S <sub>a</sub> min. | S <sub>a</sub> max. | r <sub>a</sub> min.                  | r <sub>a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 260                                    | 53.9               | 118                      | 123                 | 201                     | 177                 | 200                 | 8                   | 17.5                                 | 3                   | 2.5                       | 0.35               | 1.74           | 0.96                 | 13.0 |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| N° Ean13          | 3663952410623 |
| Diámetro interior | 100 mm        |
| Diámetro exterior | 215 mm        |
| Espesor           | 77.5 mm       |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE