

## Rodamiento conico 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>	
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.			
100	215	77.5	73	60	4	3	579	783	1 800	2 400	32320JR

  

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
260	53.9	118	123	201	177	200	8	17.5	3	2.5	0.35	1.74	0.96	13.0

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952410623
Diámetro interior	100 mm
Diámetro exterior	215 mm
Espesor	77.5 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE