

Rodamiento conico 32321-JR-JTEKT - 32321-JR-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32321-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
105	225	81.5	77	63	635	866	1 800	2 300	32321JR		

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
260	56.1	123	128	211	185	209	8	18.5	3	2.5	0.35	1.74	0.96	14.9

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952411217
Diámetro interior	105 mm
Diámetro interior	4.134" inch
Diámetro exterior	225 mm
Diámetro exterior	8.858" inch
Espesor	81.5 mm
Espesor	3.209" inch
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE