

## Rodamiento conico 30330-D-JTEKT - 30330-D-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/30330-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
150	320	72	65	46	5	4	616	750	970	1400	303300			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.		r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>
—	96.0	172	183	302	270	301	9	26	4	3	0.81	0.74	0.41	23.9

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250122521
Diámetro interior	150 mm
Diámetro exterior	320 mm
Espesor	72 mm
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE