

Rodamiento conico 32236-JR-JTEKT - 32236-JR-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/32236-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
180	320	91	86	71	957	1520	1100	1500	32236JR					
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4G0	77.8	202	204	302	267	303	10	20	4	3	0.45	1.33	0.73	29.9

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250124860
Diámetro interior	180 mm
Diámetro exterior	320 mm
Espesor	91 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE