

Rodamiento conico 535-532A-JTEKT - 535-532A-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/535-532a-jtekt>

Single-row tapered roller bearings
inch series

Koyo

Section series

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max}	<i>r</i> _{min}	<i>C</i> _r	<i>C</i> _{0r}	Grease lub.	Oil lub.

44.450	111.125	38.100	36.967	32.162	3.6	3.2	138	172	3 800	5 100
---------------	---------	--------	--------	--------	-----	-----	-----	-----	-------	-------

Bearing No.		Mounting dimensions (mm)				Constant		Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	Lead center (mm) <i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a <i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>f</i>	<i>Y</i> ₁ <i>Y</i> ₂	Inner ring Outer ring

535	532A	23.9	60.0	54.0	95.0 100.0	3.6	3.2	0.30	2.03	1.11	1.09 0.746
------------	-------------	------	------	------	------------	-----	-----	------	------	------	------------

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952427188
Diámetro interior	44.45 mm
Diámetro exterior	111.125 mm
Espesor	38.1 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE