

Rodamiento de agujas BHTM1015-JTEKT - BHTM1015-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1015-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
10	17	15	—	7.85	8.45	30 000	BHTM1015

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	9.981	10.000	16.977	16.995	12	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250003127
Diámetro interior	10 mm
Diámetro exterior	17 mm
Espesor	15 mm
Peso	12 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE