

## Rodamiento de agujas 16BTM2222B-JTEKT - 16BTM2222B-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/16btm2222b-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>			
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.		Caged type			
Full complement type						Recommended dimensions (mm)		(Refer.) Mass (g)			
With open ends		With closed end				Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
16	22	22	—	16.2	22.9	22 000				With open ends	With closed end
						15.989	16.000	21.991 <sup>4)</sup>	22.012 <sup>4)</sup>	20	—

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470344
Diámetro interior	16 mm
Diámetro exterior	22 mm
Espesor	22 mm
Peso	20 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE