

Rodamiento de agujas 20MKM2612-JTEKT - 20MKM2612-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/20mkm2612-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.	Caged type	With closed end
20	26	12	9.3	8.90	12.6	18 000	With open ends	20MKM2612

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	19.987	20.000	25.972	25.993	14	16

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470801
Diámetro interior	20 mm
Diámetro exterior	26 mm
Espesor	12 mm
Peso	16 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE